



**GARAGE DOOR OPENER
MODEL 728B**

VERSATILE CONFIDENCE

The battery backup lets you access your home even during a power outage.

- Smooth & Quiet DC Motor
- 200W Courtesy Light
- Motion Activated Lights
- Lifetime Motor Warranty



BATTERY BACKUP

When the power is out, the battery powers your opener and LED lighting keeps you safe and secure.

COMPLIES WITH CALIFORNIA SB-969

CONTROLS INCLUDED:



Deluxe Door Control Console

Open your door, turn on your lights and set remote security lock-out from one convenient location.



3-Button Remote Control

Stylish, modern design, with handy visor clip. Clear Com[®], positive click control for dependable code transmission. Controls up to three Guardian motors.

GARAGE DOOR OPENER MODEL 728B

PROSeries

SPECIFICATIONS:

Electrical/Motor

Input Voltage: 120V 60Hz
Current: 2.5A
Motor Type: 12V DC
Pull Force: 820N
Power Cord: 48in, 3-prong
ETL Listed to UL 325: Yes

Lighting

Number of Bulbs: 2
Total Wattage: 200W
Delay Duration: 4.5 mins

ClearCom® Radio Controls

Frequency:
Remote: 303/390 MHz dual frequency burst
Receiver: 303/390 MHz dual frequency agile
Coding System: Fixed, over 4 million
Operating Range (tested): 200 feet
Operating Temperature: -40°F-185°F
Code Registers: 20
Remote Control Battery: CR 2032, 3V

Battery Backup

Output: 12V
Charging Voltage/Current: 15A/1A
(with external adapter)
Recharges off-line with plug-in transformer
Operating Temperature: 14°F-122°F
Built-in Thermal Protection

Safety & Features

Down safety reversal
Up safety stop
Infra-red photo eyes
Emergency quick release
Pet/Ventilation opening
Soft-start & stop electronic learn limits
Courtesy lighting

Standard Accessories

Deluxe 3-Button remote control
Deluxe door control console

Rail and Drive

Material: Steel
Type: One-piece interchangeable, T or I
Drive: Full chain or steel reinforced drive belt
Pre-tensioned at the factory
Lubricated, maintenance free
Lengths: for 7' door height, 8' & 10' optional

Installation

Headroom clearance required: 2 in
Installed Length (std. T-rail): 127 in
Max. Door Opening (std. T-rail): 7'2"
Travel Speed: 7 in/s
Limit Setting: Electronic
Force Setting: Electronic auto-learn

Shipping Dimensions

Power Head: 22.75"x11.5"x8"; 22 lbs
Std. 7' door, T-rail, chain: 123"x3.2"x1.6"; 16 lbs
Std. 7' door, T-rail, belt: 123"x3.2"x1.6"; 14 lbs

HomeLink® compatible with all vehicles on the road today.

Lifetime Motor Warranty

1-Year on battery and all other parts.
Please refer to operator owner's manual for more details.



SAFETY & SECURITY

Guardian garage door openers are manufactured to comply with the latest industry standards. Our advanced, steel-enclosed, water-resistant, photo-eye system ensures the highest degree of reliability in detecting obstructions during operation.

CLEARCOM® TECHNOLOGY

Your secure code is communicated to your opener over multiple frequencies. This provides a more reliable response when frequency interference is near.

BATTERY BACKUP POWER SUPPLY

- Non-spillable lead-acid battery
- Status Indicator LEDs
- 2-year effective battery life
- ~300 use cycles*
- Charge time: 24 hours (trickle charge in holster)
- Power for ~20 cycles after 12-hr standby*

Item # STDBAT

*new & fully charged battery, room temperature, balanced 8'x7' door



OPTIONAL CONVENIENCE ACCESSORIES

Ask your dealer about adding more convenience and control with your new operator.

Wireless Keyless Entry Keypad

NEVER BE LOCKED OUT

An entirely weatherproof, wireless keypad that allows quick and secure access to your garage door. One keypad can control multiple Guardian garage door openers. Item # WKCC



beam SMART CONTROL KIT

CONTROL FROM YOUR SMARTPHONE

Control your garage door from your smartphone. Auto-close control. Can be retro-fit to any Guardian and most other brands. Item # V2



Guardian Access & Door Hardware
Richardson, TX 75081
www.adhguardianusa.com

HomeLink® and the HomeLink House® logo are registered trademarks of Gentex Corporation.

©2023, ADH Guardian USA LLC

BR-728B-23